



M.E.I. XCEL Xcel Cargo Entry Level 5' & 6' Wide "Xcel" Single Axle Specification

<i>Model Designation Description (width x length)</i>		MXL508SA 5' x 8'	MXL610SA 6' x 10'	MXL612SA 6' x 12'	MXL614SA 6' x 14'
Overall	Length	11' 4"	14'	16'	18'
	Width	80"	92"	92"	92"
	Height	79"	93"	93"	93"
Interior Floor	Length	90"	124"	148"	172"
Interior Floor	Width	57"	69"	69"	69"
Interior	Height	62"	74"	74"	74"
Interior Sidewall	Height	55"	67"	67"	67"
Rear Door (steel framed)	Style	Double Swinging	Double Swinging	Double Swinging	Double Swinging
	Width	49"	61"	61"	61"
	Height	5' 6"	5' 6"	5' 6"	5' 6"
Hitch	Weight	90 lbs.	130 lbs.	150 lbs.	170 lbs.
	Height	18"	18"	18"	18"
	Ball Size	2"	2"	2"	2"
Platform height		19"	19"	19"	19"
G.V.W.R.		2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.
Curb Weight (options vary actual weight)		830 lbs.	1090 lbs.	1290 lbs.	1490 lbs.
Payload Capacity		2100 lbs.	1900 lbs.	1700 lbs.	1500 lbs.
Axles (single) Spring		3500 lbs.	3500 lbs.	3500 lbs.	3500 lbs.
Brakes		Optional	Optional	Optional	Optional
Tires	Bias Ply	ST205 75/r14 (c)	ST205 75/r14 (c)	ST205 75/r14 (c)	ST205 75/r14 (c)
Wheels, modular		5 lug on 4 1/2"	5 lug on 4 1/2"	5 lug on 4 1/2"	5 lug on 4 1/2"
Frame	Steel	3" tube	3" tube	3" tube	3" tube
Floor (24" o/c floor cross members)		3/4" fir plywood	3/4" fir plywood	3/4" fir plywood	3/4" fir plywood
Side Walls (24" o/c wall studs)		1/4" Lauan	1/4" Lauan	1/4" Lauan	1/4" Lauan

Standard Features

*Spring Axle	*Welded safety chains
*E-Z lube hubs with grease caps	*Sealed beam corner post lights
*14" Bias Plyl tires	*Smooth aluminum Radius fenders
*E-coated modular wheels	*.080 Alm Extruded Roof Wraps
*Barlock Side Doors (except on 5x8)	* 3/4 " Exterior Grade Floor
*Semi style camlock door latches	*.030 beveled aluminum exterior panels (available in 13 colors)

Popular Options

Rear Ramp w/ Assist
Roof Vent
Tie Downs
13 Additional Colors
Spare Tire and Mount