



M.E.I. **XCEL** Xcel Cargo Entry Level **7' & 8.5 Wide "Xcel" Specifications**

<i>Model Designation</i> <i>Description (width x length)</i>		MXL714TA2 7'x14'	MXL716TA2 7'x16'	MXL8.5x20TA2 8.5'x20' Car Carrier	
Overall	Length Width Height	18' 6" 102" 99"	20' 6" 102" 99"	25' 6" 102" 99"	
Interior Floor	Length	14' 6"	16' 6"	20' 6"	
Interior Floor	Width	81"	81"	96" (83" between Wheel Well)	
Interior	Height	77"	77"	79"	
Interior Sidewall	Height	72"	72"	72"	
Rear Door (steel framed)	Style Width Height	Double Swinging 73 1/2" 68 1/2"	Double Swinging 73 1/2" 68 1/2"	Rear Ramp w/ Assist w/ Beavertail 90" 75"	
Hitch	Weight Height Ball Size	250 lbs. 19" 2 2/16"	270 lbs. 19" 2 2/16"	340 lbs. 20" 2 2/16"	
Platform height		20"	20"	21"	
G.V.W.R.		7,000 lbs.	7,000 lbs.	7,000 lbs.	
Curb Weight (options vary actual weight)		1860 lbs.	2110 lbs.	3060 lbs.	
Payload Capacity		5140 lbs.	4890 lbs.	3900 lbs.	
Axles (single) Spring Brakes Tires Wheels, modular Frame Floor (24" o/c floor cross members) Side Walls (24" o/c wall studs)	Bias Ply Steel	3500 lbs.(Tandem) 4 Wheel Electric ST205 75/r14 (c) 5 lug on 4 1/2" 4" Tube 3/4" fir plywood 1/4" Lauan	3500 lbs.(Tandem) 4 Wheel Electric ST205 75/r14 (c) 5 lug on 4 1/2" 4" Tube 3/4" fir plywood 1/4" Lauan	3500 lbs.(Tandem) 4 Wheel Electric ST205 75/r14 (c) 5 lug on 4 1/2" 8" I-Beam 3/4" fir plywood 1/4" Lauan	

Standard Features

*Spring Axle *E-Z lube hubs with grease caps *14" Bias Plyl tires *E-coated modular wheels *Barlock Side doors *Semi style camlock door latches	*Welded safety chains *Sealed beam corner post lights *Smooth aluminum Radius fenders * .080 Alm Extruded Roof Wraps * 3/4 " Exterior Grade Floor *.030 beveled aluminum exterior panels (available in 13 colors)
--	---

Popular Options

Rear Ramp w/ Assist (Standard on Car Carrier) Roof Vent Tie Downs 13 Additional Colors Spare Tire and Mount
